
GAEA 4





The Smarter Way To Produce

The GAEA 4 is a Bethelehem designed JU-200MC mat-supported cantilevered Jackup rated for operation in water depths of up to 200 ft and drilling depths of up to 20,000 ft. The GAEA 4 is ready for transport from the USA to its required location as and when it is needed.

Classification		Capacities	
Name	GAEA 4	Fuel	2,184 bbls
Туре	JU-200MC	Drill Water	5,992 bbls
Water Depth (ft)	200	Portable Water	1,063 bbls
Drilling Depth (ft)	20,000	Liquid Mud	1,491 bbls
Registration Country	Liberia	Bulk Tanks	6,000 cu.ft.
Current Location	Gulf of Mexico, USA	Sack Storage	3,000 sacks
Availability	Available	Variable Load (includes drilling load)	4,500 kips
		Accommodation	52 persons
		Helideck	Designed for S-61
Principal Dimensions			
		Power System	
1.1.11			

Hull	
Hull Length (ft)	157
Hull Breadth (ft)	132
Hull Depth (ft)	18
Mat	
Mat Length (ft)	220
Mat Breadth (ft)	185
Mat Depth (ft)	12 (including 2 ft skirt)
Legs	
Number of Legs	3
Туре	Tubular
Length (ft)	269.25
Size (ft)	11 (OD)
Pinholes	4 pinholes spaced 6 ft

Power System	
Main Power	3x Detroit Diesel 16V-149 TIB 1,800
	rpm / 1,750 hp engines with 3x Kato
	1,200 SR9E 600 VAC / 1140 kW
	generators
Power System	4 x 4 IPS SCR System
Emergency Power	1x Auxiliary Detroit Diesel 16V-149 TIB
	1,800 rpm / 1,750 hp engine driving a
	Kato 1,200 SR9E 600 VAC / 1,140 kW
	generator. Can be added into main
	power distribution
Cantilever	
Reach	45 ft from transom

Transversal Travel

Static Hook Load

Rotary

Setback

Max Cantilever Load

Drilling Equipment and Mud System

z i i i g z quip i i a i i i a z z z z z z i i i					
Derrick	Derrick Service International 147' x 30' x 30'				
	with a static hook load capacity of				
	750,000 lbs				
Drawworks	National 1320UE, 2,000 hp with				
	GE 752 electric motors				
Rotary Table	National C-375, with				
	1x GE 752 electric motor				
Top Drive	National Oilwell PS-500/500 Electric				
Crown Block	National 7-60FA: 500 ton				
Travelling Block	MCKISSICK: 650 ton				
Mud Pumps	2x National 12-P-160 triplex				
Shale Shakers	2x Brandt Scalpers				
	2x Derrick High Speed Cascading				
	lx Derrick Cyclone Mud Conditioner				
	1x SWACO Degasser				

BOP Equipment

DP 13–5/8" Shaffer annular preventer, 5,00	00 lb
WP, H ₂ S	trim
13-5/8" Cameron Type "U", 10,000 ps	i WP
double ram preventer, H ₂ S	trim
13-5/8" Cameron Type "U", 10,000 ps	i WP
single ram preventer, H ₂ S	trim

BOP Handling 2x JD Ingersoll Rand Hercu-link BOP handling overhead cranes with a rated capacity of 30 tons each combined capacity of 60 tons

Hoisting Equipment

ranes	lx	National	OS-105	5 Hydro	aulic
			Pedesta	l, 100 ft bo	oom
	Mc	ximum cap	pacity 25.9	2 tons at 2	25 ft
	lx	Seaking	SK-2300	Series	62
	Ну	draulic Kir	ng Post, 1	00 ft bo	oom
	М	aximum ca	pacity 37.9	tons at 2	O ft.



12 ft either side

1,000 kips

750 kips

750 kips

500 kips