

## BOSS 8



GENERAL ARRANGEMENT OUTBOARD PROFILE FLOATING CONDITION



GENERAL ARRANGEMENT OUTBOARD PROFILE

JACKED UP CONDITION WITH DERRICK SKIDDED ON SLOT DECK



The Smarter Way To Produce

The BOSS 8 is a Bethelehem designed JU-250MS mat-supported slot Jackup rated for operation in water depths of up to 250 ft and drilling depths of up to 25,500 ft. The BOSS 8 is ready for transport from the USA to its required location as and when it is needed.

Classification		Capacities	
Name	BOSS 8	Fuel	1,719 bbls
Туре	JU-250MS	Drill Water	4,575 bbls
Water Depth (ft)	250	Portable Water	474 bbls
Drilling Depth (ft)	25,500	Liquid Mud	1,806 bbls
Registration Country	Liberia	Bulk Tanks	6,030 cu.ft
Current Location	Gulf of Mexico, USA	Sack Storage	3,000 sacks
Availability	Available	Variable Load (operating	3,280 kips
		Variable Load (jacking)	2740 kips
		Variable Load (floating)	2740 kips
Principal Dimensions		Accommodation	74 persons
		Helideck	Designed for S-61
Hull			
Hull Length (ft)	166	Power System	
Hull Breadth (ft)	132	Diesel Enginer	Two (2) EMD 16-645-E8, 1950 HP
Hull Depth (ft)	16		One (1) EMD 8-645-E8, 975 HP
Mat		Generator	Three (3) EMD AB 20-6 AC
Mat Length (ft)	210		generators rated 2625 KVA, 600v
Mat Breadth (ft)	170	Emergency Generator	One (1) Cummins Model 12
Mat Depth (ft)	12 (including 2 ft skirt)		Marathon 500 KW
Legs			
Number of Legs	3	Slot	
Туре	Tubular	Reach	Drilling area from 10ft aft of slot
Length (ft)	312		bulkhead to 31.5ft aft of slot
Size (ft)	12 (OD)		bulkhead (21.5ft total)
Pinholes	6 pinholes spaced 6 ft	Transversal Travel	7.5 ft either side
		Load Capacity	1400 kips within the drilling area

Drilling	Equipment
----------	-----------

Derrick	Dreco nominal 147ft (H) with 30f
	x 30ft base. Static Hook Load
	capacity 1,300,000 lbs on 14 line
Crown Blocks	Dreco Crown Block 7427
Drawworks	National 1625DE, driven by three
	(3) EMD D79, 800 HF
Top Drive	650 ton TESCO EC
Rotary	National C-375
Travelling Block	National 760-H650
Make Up Cathead	National type "a"
Break Out Cathead	National type "a
Drill String	5

## Mud System

Mud Pumps	Two (2) National 12-P160 800HP
Shale Shakers	Two (2) Brandt King Cobra shake
	Two (2) Derrick flow line cleaner
Desilter	Fluid Systems Inc SSR 16 HIL-14
Desander	Fluid Systems Inc DSR2H 102

## BOP Equipment

BOP Stack	10,000 psi, HPHT
	Single stack 13 5/8" w/
	1x10k Annular, 1x10k single Ram,
	1x10k dual Ram
BOP Handling Crane	Letourneau 30T
Control System	Valcon 400-E30-3B60
Choke and Kill	HYD/Manual
	3-1/16" 10,000psi
Diverter	Hydril
	20" 2,000 psi

## Auxiliary Equipment

Cranes	Two (2) Letourneau PCM-120-AS w/
	100ft Boom rated 46T @ 26ft radius
Air Hoists	Two (2) units located on drill floor
	Four (4) units for tow line handling
	Two (2) units located on cellar deck
	One (1) unit in derrick to act as a
	"mule" for Derrickman
	One (1) nominal rated "Man-rider" on
	cellar deck
Watermaker	Alfa Laval Nirex JWP-36-0100
Air Compressor	Two (2) Ingersol-Rand SSR-2000
	screw type.
	One (1) Gardner Bulk air compressor.
	Three (3) Quincy 350-18
Sewage Treatment	Omnipure 12M-MX
Lifeboats	Two (2) Watercraft Covered for 44
	persons each

